

Samsung SNO-L6084RP



The main parameters	<p>Product Type : Network Camera</p> <p>Product Features : Infrared light</p> <p>Product appearance : One machine</p> <p>Imaging color : color</p>
Hardware Performance	<p>Imaging Device : 1 / 2.9 '2.19M CMOS</p> <p>Effective Pixels : 2000000</p> <p>Lens parameters : 2.8-12mm (4.3X) power zoom</p> <p>Minimum illumination : Color: 0.095Lux (1 / 30sec, F1.4), 0.002Lux (2sec, F1.4); black and white: 0Lux (IR LED on)</p> <p>Motion detection : OFF / ON (4 rectangular area)</p> <p>Other parameters : Minimum object distance: 0.5 m Focus Control: Simple Focus (power zoom) / Manual Lens Type: DC auto iris, P-Iris Mounting Type: On-board type</p>

Audio / video	Resolution : 1920x1080,1280x960,1280x720,1024x768,800x600,720x576,640x480,320x240 Compression format : H.264 (MPEG-4 Part 10 / AVC), MJPEG; G.711 u-law / G.726 Optional;
parameters	G.726 (ADPCM) 8KHz, G.711 8KHz; G.726; 16Kbps, 24Kbps, 32Kbps, 40Kbps Video frame rate : Max 30fps
Interface parameters	Audio Input : Linear input Audio output : Linear output
Other parameters	Network protocol : TCP / IP, UDP / IP, RTP (UDP), RTP (TCP), RTCP, RTSP, NTP, HTTP, HTTPS, SSL, DHCP, PPPoE, FTP, SMTP, ICMP, IGMP, SNMPv1 / v2c / v3 (MIB -2), ARP, DNS, DDNS, QoS, PIM-SM, UPnP, Bonjour safety : HTTPS (SSL) login authentication Digest login authentication IP address filtering, user access log 802.1X authentication voltage : DC 12V ± 10%, PoE Power : Maximum 7.2W Product Size : Ø260 * 78mm product weight : 1.15Kg Product color : Dark gray / metal Ambient temperature : -10-55°C