

## TEG-D 4028

4.0MP 4-IN-1 Bullet  
Camera

IR LED:  $\phi$  5X30PCS  
OV4689 + FH8538M  
1/3" OmniVision CMOS  
Sensor, 4MP/960H, With  
IR-CUT, DWDR, DNR,  
OSD



<b>Image Sensor:</b>	4MP CMOS Image Sensor
<b>Signal System:</b>	PAL   NTSC
<b>Effective Pixels:</b>	2592(H) x 1520(V)
<b>Min. Illumination:</b>	0.01 Lux @ (F1.2, AGC ON), 0 Lux with IR
<b>Shutter Time:</b>	1/25(1/30) s to 1/50,000 s
<b>Lens:</b>	2.8mm
<b>Lens Mount:</b>	M12
<b>Adjustment Range:</b>	Pan: 0 - 360°, Tilt: 0 - 75°, Rotation: 0 - 360°
<b>Day&amp; Night:</b>	IR cut filter with auto switch
<b>Video Frame Rate:</b>	2592 x 1520@20fp
<b>HD Video Output:</b>	AHD   TVI   CVI   CVBS Output
<b>Synchronization:</b>	Internal Synchronization
<b>S/N Ratio:</b>	More than 62 dB
<b>Up the Coax:</b>	Support
<b>Operating Conditions:</b>	-20 °C - 60 °C (-20 °F - 140 °F) Humidity 90% or less (non-condensing)
<b>Power Supply:</b>	12 VDC $\pm$ 15%
<b>Power Consumption:</b>	Max. 4W
<b>IR Range:</b>	Up to 25 m
<b>Dimension:</b>	155.5(W) x 72.5(H) x 71(D) mm
<b>Weight:</b>	750g