

TEG-O-028

2.0MP 4-IN-1 Bullet
Camera

IR LED: ϕ 5X24PCS
IMX323 + FH8536E
1/2.8" SONY CMOS
Sensor, 1080P/960H, With
IRCUT, Low Illumination,
DWDR, 3D NR, Sense-
up, OSD



Image Sensor:	2MP CMOS Image Sensor
Signal System:	PAL NTSC
Effective Pixels:	1930(H) x 1088(V)
Min. Illumination:	0.01 Lux @ (F1.2,AGC ON), 0 Lux with IR
Shutter Time:	1/25(1/30) s to 1/50,000 s
Lens:	2.8mm
Lens Mount:	M12
Adjustment Range:	Pan: 0 - 360°, Tilt: 0 - 75°, Rotation: 0 - 360°
Day& Night:	IR cut filter with auto switch
Video Frame Rate:	PAL: 1080p@25fp NTSC: 1080p@30fps
HD Video Output:	AHD TVI CVI CVBS Output
Synchronization:	Internal Synchronization
S/N Ratio:	More than 62 dB
Up the Coax:	Support
Operating Conditions:	-20 °C - 60 °C (-20 °F - 140 °F) Humidity 90% or less (non-condensing)
Power Supply:	12 VDC \pm 15%
Power Consumption:	Max. 4W
IR Range:	Up to 20 m
Dimension:	86(W) x 60(H) x 55(D) mm
Weight:	400g