

TEG-O-4031

2.0MP 4-IN-1 Bullet
Camera

IR LED: ϕ 28X8PCS
 IMX323 + NVP2441H
 1/2.8" SONY CMOS
 Sensor, 1080P/960H,
 With IR-CUT, Low
 Illumination, DWDR, 3D
 NR, Senseup, OSD
 3.0MP 2.8-12mm Auto
 FOCUS Lens



Image Sensor:	2MP CMOS Image Sensor
Signal System:	PAL NTSC
Effective Pixels:	1930(H) x 1088(V)
Min. Illumination:	0.01 Lux @ (F1.2, AGC ON), 0 Lux with IR
Shutter Time:	1/25(1/30) s to 1/50,000 s
Lens:	Motorized VF lens; 2.8 - 12 mm Angel of view: 26.8°-83°
Lens Mount:	M12
Adjustment Range:	Pan: 0 - 360°, Tilt: 0 - 75°, Rotation: 0 - 360°
Day& Night:	IR cut filter with auto switch
Video Frame Rate:	PAL: 1080p@25fp NTSC: 1080p@30fps
HD Video Output:	AHD TVI CVI CVBS Output
Synchronization:	Internal Synchronization
S/N Ratio:	More than 62 dB
Up the Coax:	Support
Operating Conditions:	-20 °C - 60 °C (-20 °F - 140 °F) Humidity 90% or less (non-condensing)
Power Supply:	12 VDC \pm 15%
Power Consumption:	Max. 4W
IR Range:	Up to 40 m
Dimension:	228(W) x 97(H) x 82(D)mm
Weight:	1.4Kg