



Specification:

| | |
|----------------------|-----------------------------------|
| Model No. | TGD-020 |
| Camera: | |
| Image Resolution | 1080P |
| Effective Pixels | 1920X1080 |
| Sensor | IMX291 |
| ISP | FH8550D |
| TV System | PAL/NTSC |
| Electronic Shutter | 1/25s~1/50,000s , 1/30s~1/60,000s |
| Sync System | Internal |
| Usable Illumination | 0.0001Lux |
| S/N Ratio | ≥41dB |
| Scanning System | Progressive Scan |
| Video Output Mode | AHD/TVI/CVI/CVBS (960H) OPTIONAL |
| Lens: | |
| Focus Length | Board Lens 2.8mm |
| Pixels | 3MPixels |
| Night Vision: | |
| Infrared LED | 14μX12PCS |

| | |
|-------------------------|--|
| Infrared Distance | 20M |
| IR Status | Under 10 Lux by CDS |
| IR Power On | CDS Auto Control |
| Camera Features: | |
| Day/Night | Auto (ICR) / Color / B&W |
| OSD Menu Language | EN, CN, DE,FRA, IT, ES, PL, RU, PT, NL, TR |
| White Balance | Auto/ Manual |
| Gain Control | Auto |
| Noise Reduction | 3D NR |
| Picture Adjustment | YES |
| OSD Support | YES |
| General: | |
| Weatherproof Housing | N/A |
| Anti-cut Bracket | N/A |
| IR Cut Filter | YES |
| Operation Temperature | -10°C ~ +50°C RH95% Max |
| Storage Temperature | -20°C ~ +60°C RH95% Max |
| Power Source | DC12V±10%, 260mA |
| Dimension | ϕ 94 x 69(H) mm |
| Weight | 370g |

Made in China.